

RECESSED COMBO THREE-IN-ONE

Model # 64674



American Specialties' Three-in-One Paper Towel Dispenser with Waste Receptacle and Automatic Electric Hand Dryer has Gone High-Speed

American Specialties, Inc. introduces the new three-in-one paper towel dispenser with waste receptacle and automatic hand dryer, featuring the TURBO-Dri™ Jr. (model #0198). The compact **high-speed** hand dryer is a perfect fit for this unit.

- Quick drying — less than 15 seconds
- Operates automatically using infrared sensor
- Auto-resetting thermostat
- 60-second automatic shut off

To keep the paper towels in the waste receptacle from blowing out, a spring-loaded lid has been added.

Also available for semi-recessed and surface mounting.

Other New American Specialties Hand Dryers



TURBO-Tuff™



TURBO-ADA™



TRI-Umph™



SPECIFICATIONS

Recessed Combo Three-in-One Paper Towel Dispenser with Waste Receptacle and Automatic Electric Hand Dryer shall hold and dispense 800 standard multi-fold or 600 standard C-fold or 1100 standard single fold paper towels and shall have a waste capacity of 4 gal (15 L). An adjustable guide shall be provided to allow dispensing of single-fold, multi-fold or C-fold paper towels. Cabinet, door, dispenser and waste receptacle (WR) shall be type 304 stainless steel alloy 18-8. All exposed surfaces shall have satin finish and shall be protected during shipment by PVC film easily removable after installation. Cabinet shall be 20 gauge with 7/8" (22) wide perimeter trim to lay flush against wall and shall have no exposed fastening devices or visible seams. Full-face door shall be 18 gauge, fabricated from one piece with no miters or seams on face and shall have 1/2" (13) square returns to the wall. Door shall be attached to cabinet body with a full length 3/16" diameter (Ø4.8) stainless steel multi-staked piano hinge and shall be held closed with two (2) tumbler locks keyed alike to other ASI washroom equipment. Towel dispensing slot shall have a fully hemmed-in rolled edge for snag-free dispensing and user safety. WR shall have spring-hinge mounted closed top with hemmed bottom edge for safety. Structural assembly of all cabinet components shall be of welded construction. Hand Dryer shall operate automatically from IR sensor that shall activate dryer when hands are placed in sensor zone. Complete dryer specification and warranty information is contained in the Model # 0198 TDS. Complete dryer Owner's Manual (OM) and Installation Guide (IG) shall be provided with unit.

WALL OPENING: 12" W x 54-1/4" H x 6-1/2" (305 x 1378 x 165)

MODEL	TYPE	VOLTS@ 50/60 Hz	AMPS	WATTS	DRYING TIME	COVER
64674	Fixed nozzles for hands	110 ~ 120	8.33	1000	Automatic, Less than 15 seconds	Satin Finish; Vertical Grain; 304 Stainless Steel
64675		220 ~ 240	4.17	1000		

AIR SPEED	MOTOR	H/P	RPM x 1000	FAN TYPE	AIR FLOW	HEATING ELEMENT	OUTPUT AIR TEMPERATURE
295 ft/s [201 mi/h] (90 m/s [324 km/h])	Brush Type Dual Ball Bearings with 275°F (135° C) auto reset circuit breaker	0.67	29	Multi Inlet Centrifugal	60 CFM (102m ³ /h)	500 W Nichrome wire with auto reset circuit breaker and thermostat	131° F (55° C) @ 77° F (25° C) ambient room temperature



American Specialties, Inc.
441 Saw Mill River Rd, Yonkers, NY 10701
Tel: 914.476.9000 Fax: 914.476.0688
E-mail: info@americanspecialties.com Web: americanspecialties.com